

CX410

2K PoE IP camera with ColorX True Full-Color Night Vision, F1.0 Aperture, and Smart Detection.

- True Color Night Vision in the Darkest Night
- F1.0 Super Aperture
- 3000K Adjustable Warm Light



Specifications

Video & Audio	
Image Sensor	1/1.8" CMOS Sensor
Video Resolution	2560×1440 (4.0 Megapixels)@25fps
Lens	f=4mm; F=1.0
Video Format	H.264
Field of View	Horizontal: 89°; Vertical: 46°
Color Night Vision	4pcs/3W/3000K/400 lumens
Audio	Two-way audio
Power	
PoE	IEEE 802.3af, 48V active
DC Power	DC 12.0V 1A, <12W
Interface	
Power	DC 12V 1A & PoE
System	Reset button

Ethernet	One 10M/100Mbps RJ45
Storage	microSD card slot (Max. 256GB)
Audio	Built-in microphone & speaker
Software Features	
Frame Rate	Main stream: 2fps - 30fps (default: 25fps); Sub stream: 4fps - 15fps (default: 10fps)
Code Rate	Main stream: 2048Kbps - 6144Kbps (default: 5120Kbps); Sub stream: 64Kbps - 512Kbps (default: 256Kbps)
Browser Supported	Edge, Chrome, Firefox, Safari
OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android
Smart Alarm	Motion detection; person detection; vehicle detection; animal detection
Record Mode	Motion recording (default); schedule recording; 24/7 recording
Protocols & Standards	HTTPS, SSL, TCP/IP, UDP, IPv4, UPnP, RTSP, RTMP, ONVIF, SMTP, NTP, DHCP, DNS, DDNS, FTP, P2P
Maximal User Access	20 Users (1 admin account & 19 user accounts); Up to 12 simultaneous video streams (10 sub streams & 2 main streams)
Work with	Google Assistant
Working Environment	
Temperature	-10°C to +55°C (14°F to 133°F)
Humidity	10% – 90%
Weatherproof	IP67
Size & Weight	
Dimensions	Φ67×187mm
Weight	480g
Warranty	
Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/

Gallery & Specs



1. Bracket
2. Speakers
3. Aluminum Housing
4. Lens
5. Spotlight



1. microSD Card Slot



1. Turn the adjustment knob (counter-clockwise) to loosen the bracket and adjust the camera in any direction.
2. Turn the adjustment knob back after adjustment to fix the camera.



1. Power
2. Reset Button
3. Network

