

RLK8-833D4-A

4K 3X Optical Zoom Smart PoE Security Camera System with 2TB HDD & 8CH NVR for 24/7 Recording

- 4K UHD & 3X Optical Zoom
- Color Night Vision
- 2TB HDD 8-Channel NVR



Specifications


RLC-833A	
Video & Audio	
Image Sensor	1/2.8" CMOS sensor
Video Resolution	Default: 3840*2160 (8 megapixels) @25FPS
Lens	f=2.8-8mm, F=1.6, with IR Cut
Video Compression	H.264/H.265
Field of View	Horizontal: 94°- 50° Vertical: 53°- 30°
Day & Night	IR-cut filter with auto-switching
Infrared Night Vision	30 meters (2pcs/28mil/850nm)
Color Night Vision	1pcs/4.7W/6500K/700lm
Audio	Two-way audio
Power	
PoE	IEEE 802.3af, 48V active

DC Power	DC 12.0V 1A, <12W
Interface	
Power	DC power port
System	Reset button
Ethernet	One 10M/100Mbps RJ45
Storage	microSD card slot (max. 256GB)
Audio	Built-in microphone and speaker
Software Features	
Frame Rate	Mainstream: 2fps - 25fps (default: 25fps) Substream: 4fps - 15fps (default: 10fps)
Code Rate	Mainstream: 4096Kbps - 8192Kbps (default: 6144Kbps) Substream: 64Kbps - 512Kbps (default: 256Kbps)
Browser Supported	Edge, Chrome, Firefox, Safari
OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android
Smart Alarm	Motion detection, person detection, vehicle detection, pet detection
Record Mode	Motion recording (default), scheduled recording, 24/7 recording
Protocols & Standards	HTTPS, SSL, TCP/IP, UDP, HTTP, IPv4, UPnP, RTSP, RTMP, ONVIF, SMTP, NTP, DHCP, DNS, DDNS, FTP, P2P
Maximum User Access	20 users (1 admin account and 19 user accounts); 12 simultaneous video streams (10 substreams and 2 mainstreams)
Work with	Google Assistant
Working Environment	
Operating Temperature	-10°C~+50°C (14°F~122°F)
Operating Humidity	10% ~ 90%
Weatherproof	IP67
Size & Weight	
Dimensions	Φ117.4 x 103.8mm

Weight	510g
Warranty	
Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/
RLN8-410	
Hardware	
Hardware	N7MB01
Video/Audio Input	
IP Video Input	Up to 12 IP cameras (max.8 wired cameras)
Audio Input	Cameras with built-in mic
Video/Audio Output	
Video Output	VGA, HDMI
Audio Output	1-channel, RCA
Hardware Features	
Display Resolution	HDMI: 3840x2160, 1920x1080, 1280x1024, 1280x720, 1024x768 VGA: 1920x1080, 1280x1024, 1280x720, 1024x768
Decoding	
Live View/Playback Resolution	7680×2160, 4608×1728, 4512×2512, 4096×3072, 3840×2160, 2560×2560, 2560×1920, 2560×1440, 2048×1536, 2304×1296, 1080p, 720p
Video Format	H.264, H.265
Synchronous Playback	Up to 4 channels
HDD	
SATA	1 x SATA interface (1 x 2TB HDD included)
Capacity	Up to 12TB (max. 6TB capacity for each HDD)
External HDD	1 eSATA interface for HDD
External Interface	
USB Interface	2 x USB 2.0

Network Interface	1, RJ-45 10/100 Mbps self-adaptive Ethernet interface for LAN/WAN 8, RJ-45 10/100 Mbps self-adaptive PoE Ethernet interface for IP camera
PoE	
Max. Power Per Port	25W
Supported Standard	IEEE 802.3af/at
Network	
Network Protocols	HTTP, TCP/IP, UDP, DHCP, P2P, UPNP, RTSP, SMTP, SSL/TLS, DNS, DDNS, NTP, FTP
Browsers Supported	Edge, Firefox, Chrome, Safari
OS Supported	PC: Windows, Mac OS; smartphone: iOS, Android
Max. User Access	20 users (1 admin account & 19 user accounts); supports up to 12 simultaneous video streams (10 substreams & 2 mainstreams)
General	
Power Supply	DC 48V~53V
Power Consumption	<10W (without HDD & PoE)
Working Environment	Temperature: -10°C~+45°C (14°F~113°F); humidity: 10%~90%
Dimensions	260 x 41 x 230mm
Weight	1.4kg
Warranty	
Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/ .

Gallery & Specs




1. Mount
2. Metal Aluminum Case
3. Spotlight
4. IR LEDs
5. High Definition Lens
6. Daylight Sensor
7. Built-in Mic
8. Speaker




Manual rotation only.



1. Power
2. Reset Button
3. Network



1. USB Port
2. Power LED/HDD LED
3. Control Panel



1. On/Off Switch
2. eSATA
3. RJ45
4. Power Input
5. Audio Out
6. USB Port
7. HDMI Port
8. VGA Port
9. Network

www.reolink.com